

Revised EU Ecolabel protocol for testing laundry detergents

Content

- 0. Background
- 1. Test criteria
- 2. Laboratory requirements to conduct the testing.
- 3. Materials and conditions
- 4. Methods
- 5. Evaluation
- Annex 1. Example

Abbreviations

| | | | |
|--------|---------------------------|------|-------------------------------|
| HDD | Heavy duty detergent | DTI | Dye transfer inhibition |
| CSD | Colour safe detergent | SBL | Soil ballast load |
| LDD | Light duty detergent | PC | Sodium percarbonate |
| SR | Stain removal | TAED | Tetra acetyl ethylene diamine |
| BDW | Basic degree of whiteness | PVP | Polyvinylpyrrolidone |
| CM | Colour maintenance | CO | Cotton |
| PA | Polyamide | PES | Polyester |
| PES/CO | Polyester/cotton | WO | Wool |
| SI | Silk | | |

0. Background

This test protocol serves as a means of proof to show compliance with the criterion "Fitness for use" of the Commission Decision (EU) 2017/1218 of 23 June 2017 establishing EU Ecolabel criteria for "Laundry detergents". The product shall be fit for use, meeting the needs of users.

The test is for products that fall under the scope of the product group "Laundry detergents", which includes laundry detergents and stain removers. For each of these products, a different performance test is published, as specified in the Section 3.1 "Range of application".

The performance test for laundry detergents shall show that laundry detergents achieve good washing performance according to soil and stain removal, basic degree of whiteness, colour maintenance and dye transfer inhibition criteria. The product shall meet the requirements for wash performance set out in all the criteria listed in Section 1.

1. Test criteria

- soil and stain removal (SR)
- basic degree of whiteness (BDW)
- colour maintenance (CM)
- dye transfer inhibition (DTI)

2. Laboratory requirements to conduct the testing.

The manufacturer's test laboratory or/and an external test laboratory can be approved to conduct testing to document effectiveness of laundry detergents if the following requirements are met:

- it must be possible for EU Ecolabel competent bodies to monitor the performance of testing (e.g. on-site visits to the laboratory),
- the EU Ecolabel Competent Body must have access to all data on the product (e.g. technical data sheets),

- whenever possible, the samples must be made anonymous for the test laboratory (e.g. product A and product B).
- the test laboratories must be equipped with the devices described in the test method,
- performance of the effectiveness test as well as the test method must be described in the quality control system.

Competent bodies shall preferentially recognise attestations which are issued by bodies accredited in accordance with the relevant harmonised standard for testing and calibration laboratories and verifications by bodies that are accredited in accordance with the relevant harmonised standard for bodies certifying products, processes and services. Accreditation shall be carried out in accordance with Regulation (EC) No 765/2008 of the European Parliament and of the Council

3. Materials and conditions

The test institute must be able to prove compliance with all the test conditions laid down in the following paragraphs. Documentation demonstrating compliance with all the test conditions shall be part of the test report.

3.1 Range of application:

In the context of the EU Ecolabel, this performance test can be applied to the following types of laundry detergents and stain removers:

- Heavy-duty detergent (HDD) means a detergent used for ordinary washing of white textiles at any temperature
- Colour-safe detergent (CSD) means a detergent used for ordinary washing of coloured textiles at any temperature
- Light-duty detergent (LDD) means a detergent intended for delicate fabrics

3.2 Washing machine types:

Programmable electronic Miele¹ household washing machines which fulfil the following requirements:

Table 1. Washing machine and wash programmes specifications

| | Cotton wash program (at 30 °C, 20 °C ^a , 15 °C ^b) | Delicate program ⁿ (at 30 °C, 20 °C ^a , 15 °C ^b) |
|--------------------------|---|---|
| Duration main wash | 50-70 min | 30-40 min |
| Total program duration | 100-120 min | 55-65 min |
| Water quantity main wash | 15±2 l | 20±2 l |
| Total water quantity | 55±5 l | 64±5 l |
| Number of rinse cycles | 3 | 3 |
| Final spin speed | 1200 rpm ² | 600 rpm |

^a for cold water products

^b most of the older machines do not offer cold water programs. Those machines which offer cold water programmes normally heat up the entering water to 21 °C, which can be used for products that claim to be effective at 20 °C. For test runs at 15 °C the heating elements of the washing machine have to be disconnected to prevent the heat up

ⁿ some newer washing machines offer an equivalent synthetic program

Fuzzy logic type control shall be disabled.

3.3 Water conditions:

¹ Miele machine was proposed as a reference machine due to its stable performance and regular quality of the outcomes.

For use in laboratories Miele launched a special line of machines where the fuzzy logic is already disabled (e.g. Miele 1935 WPS WTL).

Another machine could be used as reference machine if it provides similar performance for a comparable programme.

² Other spin can be used but it should be at least 900 rpm

Water hardness: $2,5 \pm 0,2$ mmol CaCO_3/l . The Ca/Mg ratio shall be $3 \pm 0,5$.

Water inlet temperature: $20,0 \pm 4,0$ °C, except for those products that claim to be effective at lower temperatures. The water inlet temperature for products that claim to be effective at lower temperatures shall be $15,0 \pm 4,0$ °C, but the reference product shall be tested in this case at $20,0 \pm 4,0$ °C.

The amount of water shall be controlled along the washing process, if possible.

The water hardness and the water inlet temperature shall be reported for the test product and reference detergent.

3.4 Ballast load:

For HDD and CSD: cotton ballast load.


The base load of cotton shall consist of cotton pillowcases and cotton huckaback towels conforming the IEC 60456 "Clothes washing machines for household use – Methods for measuring the Performance"³

For LDD: polyester ballast load.

The base load shall consist of double knitted polyester in pieces conforming to the following specifications⁴.

Table 2. Ballast load for LDD

| | Knitted polyester fabric. |
|--------------------|---|
| Mass | 35 ± 3 g |
| Mass per unit area | 200 ± 25 g/m ² |
| Pieces | 30±3cm x 30±3cm, double layer sewn along all four edges |



3.5 Stains set

Current AISE stain set as described in Section 3.9.c. 2 sets of stains per wash cycle (in the same batch) should be used. Mark with a water resistant pen each stain as the Figure 1. Fix the stains on the loads with a plastic staple with a gun on the load, as shown in Figure 2 and Figure 3.

See Figure 4 for an example of how the stains can be fixed.

³ Examples of commercial article codes are W-IEC T13 or E-353 for cotton pillow cases and W-IEC T12 or E-351 for Huckabeck Towels

⁴ Examples of commercial article codes are W-IEC or E-356




Figure 4. Fixed stains on the load (example)

Abbreviations stand for the type of soiling as indicated in Table 10.

Alternatively, the stains can be stitched together beforehand to make a full test strip. Then, this strip must be fixed on a hand towel before washing.

Other possibilities are to use a ready to use monitor⁵

3.6 Stains set size

(12x12) cm² (standard stains), 35x45cm AISE multiswatch monitors with 5x5cm swatches and 5 cm diameter (hand-made).

3.7 Soil

SBL 2004's can be fixed on the loads as the stains.

Table 3. SBL's use

| HDD & CSD | | LDD | |
|---|---------------------|---|---------------------|
| Stain removal & basic degree of whiteness | Colour maintenance | Stain removal & basic degree of whiteness | Colour maintenance |
| 4 units of SBL 2004 | 2 units of SBL 2004 | 2 units of SBL 2004 | 2 units of SBL 2004 |

3.8 Dye donators and dye acceptors to determine dye transfer

3.8.1 Dye donators:

- E-132 cotton dyed with direct black 22 (weight 0,3g => 5x6 cm)
- E-134 cotton dyed with direct orange 39 (weight 0,3g => 5x6 cm)
- E-130 cotton dyed with direct red 83,1 (weight 0,3g => 4,5 x 4,5 cm)
- E-131 cotton dyed with acid blue 113 (weight 0,3g => 5x10 cm)

3.8.2 Dye acceptors:

- standard cotton according to ISO 2267 or DIN 53919, as for instance W-10A (size 5,5x16 cm)
- polyamide according to ISO 105 F03 (as for instance W-40 or T-ADJ polyamide) (size 6x16 cm)

3.9 Wash loads

Each series of tests shall be started with a new wash load. This load consists of:

a) Stain removal & basic degree of whiteness for HDD/CSD (powder and liquid)

1. A new all cotton ballast load for the normal cotton wash program to reach a total weight of 4,5 kg(.

Table 4. Ballast load for testing the whiteness for HDD/CSD (powder and liquid)

| Total load (kg) | Pillowcases | Hand-towel |
|-----------------|-------------|--------------|
| 4,5 kg ± 0,1kg | 12 units | Until weight |

⁵ Examples of ready to use monitors at the time of writing are:

- Multiwatch monitors from Empa (Swissatest), WFK or CFT
- Multistain monitors from Equest or CFT with the handmade stains directly applied on the fabric
- Multiwatch monitor with a combination of standard swatches in combination with handmade stains cut out and sewn as well.

2. 2 standard cotton cloths, according to ISO 2267 or DIN 53919 (size 20x20 cm)
3. 14 stain removal monitors included in the washes 6 to 11 x2 replicates
4. 4 pieces of soil ballast added to all washes

The total load per wash including ballast load, SBL 2004, cotton cloth and monitors shall be 4,5 ±0,1 kg.

Table 5. Wash load for HDD and CSD (powder and liquid). Test: stain removal and basic degree for whiteness

| Test | | Pre-treatment | | | Basic degree of whiteness | | | | | Stain removal & basic degree of whiteness | | | | | | Basic degree of whiteness | | | |
|-------|---|---------------|----|----|---------------------------|---|---|---|---|---|---|---|---|----|----|---------------------------|----|----|----|
| cycle | | -3 | -2 | -1 | 1 | 2 | 3 | 4 | 5 | 6 | 7 | 8 | 9 | 10 | 11 | 12 | 13 | 14 | 15 |
| loads | Cotton ballast load* | x | x | x | x | x | x | x | x | x | x | x | x | x | x | x | x | x | x |
| | Cotton cloth according to ISO 2267** | x | x | x | x | x | x | x | x | x | x | x | x | x | x | x | x | x | x |
| | Stain set (14 stains x 2 sets per wash, cycle 6-11) | | | | | | | | | x | x | x | x | x | x | | | | |
| | Soil: 4 units SBL2004 | | | | x | x | x | x | x | x | x | x | x | x | x | x | x | x | x |

*use the same wash load during all the test

** use the same cotton cloth during all the test

b) Colour maintenance for HDD/CSD (Powder and liquid)

1. A new all cotton ballast load for the normal cotton wash program to reach a total weight of 4,5kg.

Table 6. Ballast load for testing colour maintenance for HDD/SCD (powder and liquid)

| | | |
|-----------------|-------------|--------------|
| Total load (kg) | Pillowcases | Hand-towel |
| 4,5 kg ±0,1kg | 12 units | Until weight |

2. Colour maintenance monitor
3. 2 pieces of soil ballast added to all washes

The total load per wash including ballast load, SBL 2004, cotton cloth and monitors will be 4,5 ±0,1kg

Table 7. Wash load for HDD (only if claimed) and CSD (powder and liquid). Test: colour maintenance

| Test | | Pre-treatment | | | Colour maintenance | | | | | | | | | | | | | | |
|-------|--|---------------|----|----|--------------------|---|---|---|---|---|---|---|---|----|----|----|----|----|----|
| Cycle | | -3 | -2 | -1 | 1 | 2 | 3 | 4 | 5 | 6 | 7 | 8 | 9 | 10 | 11 | 12 | 13 | 14 | 15 |
| loads | Cotton ballast load* | x | x | x | x | x | x | x | x | x | x | x | x | x | x | x | x | x | x |
| | Colour maintenance monitor See Table 8** | | | | x | x | x | x | x | x | x | x | x | x | x | x | x | x | x |
| | Soil: 2 units SBL2004 | | | | x | x | x | x | x | x | x | x | x | x | x | x | x | x | x |

*use the same wash load during the entire test

** use the same cloth during the entire test

The colour maintenance monitor sets are shown in Table 8:

Table 8. Monitor dye set

| Fabric number of AISE Monitor dye set | Fabric number of AISE Dye set | Dye Class |
|---------------------------------------|-------------------------------|---|
| AISE 1 | 1 | Sulphur black |
| AISE 3 | 2 | Vat green |
| AISE 5 | 3 | Vat blue |
| AISE 8 | 4 | Direct yellow + cationinc after-treatment (tinofix eco) |

| | | |
|---------|----|-----------------------------------|
| AISE 16 | 5 | Reactive red |
| AISE 20 | 6 | Reactive black (pale shade) |
| AISE 21 | 7 | Reactive black (heavy shade) |
| AISE 22 | 8 | Reactive orange |
| AISE 24 | 9 | Reactive blue |
| AISE 26 | 10 | Reactive violet |
| AISE 27 | 11 | Reactive trichromatic combination |
| AISE 29 | 12 | Reactive trichromatic combination |
| AISE 33 | 13 | Disperse navy + heat set |
| AISE 39 | 14 | Acidic red + syntan |

c) Stain Removal & basic degree of whiteness for LDD

1. A new knitted polyester load for the normal delicate wash programs to reach a total weight of 2,5kg (see Table 2)

2. 2 standard cotton clothes, according to ISO 2267 or DIN 53919, (size 20x20 cm)

3. 14 stain removal monitors included in the washes 6 to 11 x2 replicates

4. 2 pieces of soil ballast added to all washes

The total load per wash including ballast load, SBL, cotton cloth and monitors will be $2,5 \pm 0,1$ kg

Table 9 Wash loads for LDD (Powder and liquid). Test: stain removal and basic degree of whiteness

| Test | | Pre-treatment | | | Basic degree of whiteness | | | | | Stain removal & basic degree of whiteness | | | | | | Basic degree of whiteness | | | |
|-------|---|---------------|----|----|---------------------------|---|---|---|---|---|---|---|---|----|----|---------------------------|----|----|----|
| Cycle | | -3 | -2 | -1 | 1 | 2 | 3 | 4 | 5 | 6 | 7 | 8 | 9 | 10 | 11 | 12 | 13 | 14 | 15 |
| loads | Polyester ballast load* | x | x | x | x | x | x | x | x | x | x | x | x | x | x | x | x | x | x |
| | Cotton cloth according to ISO 2267** | x | x | x | x | x | x | x | x | x | x | x | x | x | x | x | x | x | x |
| | Stain set (14 stains x 2 sets per wash, cycle 6-11). See Table 10 | | | | | | | | | x | x | x | x | x | x | | | | |
| | soil: 2 units SBL2004 | | | | x | x | x | x | x | x | x | x | x | x | x | x | x | x | x |

*use the same wash load during all the test

** use the same cotton cloth during all the test

The stain sets are shown in Table 10.

Table 10. Set of stain

| Figure 5 | Stain | Standard stain | | | Hand-mad stains* | Stain classes** |
|----------|------------------------|----------------|---------|-------------|------------------|--|
| TE | Tea | | WFK 10J | | WE5LTWKC | Drink/bleachable |
| CO | Coffee | | | CFT KC H109 | WE5LCWKC | Drink/bleachable |
| RW | Red wine | | | CFT KC H026 | WE5RWWKC | Drink/bleachable |
| FJ | Fruit juice | | | CFT CS15 | | Drink/bleachable |
| TP | Tomato puree | | | | WE5TPWKC | Food/bleachable |
| CBF | Carrot baby food | | | | WE5IACBWKC | Food/bleachable, enzymatic |
| FSM | French squeeze mustard | | | | WE5FSMWKC | Food/bleachable, enzymatic, |
| CO | Chocolate | | WFK 10Z | CFT CS44 | | Food/ enzymatic |
| GR | Grass | EMPA 164 | | CFT CS08 | | General soil /bleachable, enzymatic, |
| GR/MU | Grass/mud | | | | WE5GMWKC | Grease, oil / bleachable, enzymatic, particulate |

| | | | | | | |
|-----|-------------------------------|------------|----------|----------|---------------------------------------|----------------------------------|
| BL | Blood | | | | WE5DASBWKC | General soil / enzymatic |
| UMO | Unused motor oil | EMPA 106 | WFK 10RM | CFT C-01 | | Grease, oil/ greasy, particulate |
| FF | Frying fat (hamburger grease) | | | | Burnt beef WE5BBWKC (on white cotton) | Grease, oil/ greasy, enzymatic |
| MU | Make up | EMPA 143/2 | WFK 10MU | CFT CS17 | | Cosmetics/ greasy, particulate |

* (ex Warwick-Equest) All hand-made stains are also available in 2.5 cm diameter. Their code has "2.5" instead of "5"

** (consumer denomination / chemical nature)

d) Colour maintenance for LDD

1. A new knitted polyester load for the normal delicate wash programs to reach a total weight of 2,5kg (see, Table 2)

2. Colour maintenance monitor

3. 2 pieces of soil ballast added to all washes

The total load per wash including ballast load, SBL, cotton cloth and monitors will be 2,5 ±0,1 kg

Table 11. Wash loads for LDD (powder and liquid). Test: colour maintenance

| Test | | Pre-treatment | | | Colour maintenance | | | | | | | | | | | | | | |
|-------|---|---------------|----|----|--------------------|---|---|---|---|---|---|---|---|----|----|----|----|----|----|
| Cycle | | -3 | -2 | -1 | 1 | 2 | 3 | 4 | 5 | 6 | 7 | 8 | 9 | 10 | 11 | 12 | 13 | 14 | 15 |
| loads | Polyester ballast load* | x | x | x | x | x | x | x | x | x | x | x | x | x | x | x | x | x | x |
| | Colour maintenance monitor. See Table 8** | | | | x | x | x | x | x | x | x | x | x | x | x | x | x | x | x |
| | soil: 2 units SBL2004 | | | | x | x | x | x | x | x | x | x | x | x | x | x | x | x | x |

*use the same wash load during the whole test

** use the same cloth during the whole test

3.10 Dosage

In the case of powder detergents dose detergent in the dispenser machine device, and in the case of liquid detergents dose detergent in the tumble using a plastic dosage unit.

Table 12. Detergent dosage

| Type of detergent to test | Reference detergent | | | | Market detergent According to producer recommendation. |
|---------------------------|---------------------|---------------------|------|------|--|
| | Basic powder | Sodium percarbonate | TAED | PVP* | |
| Powder HDD | 70g | 12,5g | 2,5g | - | Medium soil/medium hard water recommendation. The dosage needs to comply with the Ecolabel criteria |
| Liquid HDD | 70g | | | - | |
| Powder and liquid CSD | 70g | - | - | 1ml | |
| Powder and liquid LDD | 35ml | | | | Light soil/medium hard water recommendation. The dosage needs to comply with the Ecolabel criteria |

* active substance: 45%, PVP IV, 30% (Sokolan HP 56K)

3.11 Reference detergent

Table 13. Reference detergents

| Type of detergent | Reference detergent | | | |
|---|--|-------------------|-----------------|-------------|
| HDD | <p>Regular standard powder detergent IEC P (that can serve as reference for a detergent to wash white fabrics). This standard detergent is distributed as three separate components (because of stability of storage) with the following composition:</p> <ul style="list-style-type: none"> - 82% IEC P BASE powder with enzyme and foam inhibitor (= IEC-A* BASE powder see table below) - 15% sodium percarbonate - 3% bleach activator tetra-acetythylenediamine (TAED) | | | |
| | Ingredient | % content | Tolerance (+/-) | CAS n. |
| | linear sodium alkyl benzene sulfonate | 11,4 | 0,5 | 25155-30-0 |
| | ethoxylated fatty alcohol C _{12/14} (7EO) | 6,1 | 0,3 | 68439-50-9 |
| | sodium soap (tallow soap) | 4,2 | 0,2 | 308075-99-2 |
| | foam inhibitor concentrate, 12% silicon on inorganic carrier) | 5,1 | 0,3 | 68989-22-0 |
| | sodium aluminium silicate zeolite 4A (80% active substance) | 36,7 | 1 | 70955-01-0 |
| | sodium carbonate | 15,1 | 1 | 497-19-8 |
| | sodium salt of a copolymer from acrylic and maleic acid (sokalan CP5) | 3,1 | 0,2 | 60472-42-6 |
| | sodium silicate (SiO ₂ :Na ₂ O = 3.3:1) | 3,9 | 0,2 | 1344-09-8 |
| | carboxymethylcellulose | 1,6 | 0,1 | 9004-32-4 |
| | phosphonate (25% active acid) | 3,6 | 0,2 | 22042-96-2 |
| | protease | 0,5 | 0,5 | 9014-01-1 |
| | sodium sulfate | rest | rest | 7757-82-6 |
| <p>Homogenize powder detergent, better with a sample divider or if not shake the detergent gently. The ingredients shall be mixed prior to use. The maximum storage time after mixing is 7 days Dosage for powder HDD: 70g IEC P BASE + 12.5g sodium percarbonate (CAS 15630-89-4) + 2.5g TAED (CAS 10543-57-4) Dosage for liquid HDD: 70g IEC P BASE</p> | | | | |
| LDD | Ingredient | % technical grade | Tolerance (+/-) | CAS n. |
| | fatty alcohol ethoxylate C _{12/14} (EO=7) ^a | 35 | 0,5 | 68213-23-0 |
| | low foaming fatty alcohol C _{12/14} with approx 4mol EO and approx 5 moles PO (ethyleneoxide/higher alkylene oxide -co-polymer) ^b | 15 | 0,3 | 68439-51-0 |
| | sodium dodecyl sulfonate ^c | 7,5 | 0,2 | 68411-30-3 |
| | modified polycarboxylate (suitable for liquid detergents) ^d | 15 | 0,3 | |
| | ethanol | 5 | 0,1 | 64-17-5 |
| | distilled water add to 100% | rest | | |

| | |
|-----|--|
| | Manufacturing process: 1. Mix fatty alcohol ethoxylate C12/14 (EO=7) and sodium dodecyl sulfonate heating to 40 °C 2. When the mixture will be homogenized, add low foaming fatty alcohol ethoxylate. Mix and homogenize 3. Add ethanol 4. Add modified polycarboxylate and mix 5. Finally, add water (until 100%) The bottle shall be agitated before use Dosage, power or liquid LDD: 35ml/wash cycle |
| CSD | Reformulation of the IEC P BASE reference detergent according to IEC 60456 formulation Dosage: 70g IEC P BASE + 1ml PVP (PVP VI, Sokalan HP 56 K) |

^a example: dehydol LT-7 (BASF)

^b example: dehypon LS 45 (BASF)

^c example: maranil paste A55 (BASF)

^d example: sokalan HP 25 (BASF)

3.12 Number of cycles

A set of 15 washing machine cycles for the determination of:

- stain removal testing from cycle nr 6 to cycle nr 11- final Y-value (HDD/CSD/LDD)
- basic degree of whiteness- final Y-value (HDD/CSD/LDD)

A separate set of 15 additional cycles, run separately for colour maintenance CSD and HDD/LDD (only in the case that colour care is claimed),

Grey scale determination.

Dye transfer inhibition: for CSD and HDD/LDD (only in the case that colour care is claimed), 3 replicates with new dyes donators and acceptors in each wash. Grey scale determination.

Table 14. Cycles for each type of products

| | Colour claim | Stain removal | Basic degree of whiteness | Colour maintenance | DTI |
|-----|--------------|---------------|---------------------------|--------------------|-----|
| HDD | Yes | ✓ | ✓ | ✓ | ✓ |
| | No | ✓ | ✓ | x | x |
| CSD | | ✓ | ✓ | ✓ | ✓ |
| LDD | Yes | ✓ | ✓ | ✓ | ✓ |
| | no | ✓ | ✓ | x | x |

3.13 Wash programme

Table 15 shows the different wash programmes for the Ecolabel performance test.

With low temperature and cold-water wash products, the washing performance will be determined at the lowest stated temperature at which the detergent is claimed to be effective. The reference detergent should be tested at 30 °C.

Table 15. Different wash programs

| Test product | Temp efficient | Wash programme test product | Wash programme reference detergent | Water inlet temperature test product | Water inlet temperature reference detergent | Heating Element* |
|--------------|----------------|---------------------------------------|---------------------------------------|--------------------------------------|---|------------------|
| HDD/CSD | 30 °C | 30 °C, normal cotton program, 1200rpm | 30 °C, normal cotton program, 1200rpm | 20,0 ± 2,0 °C | 20,0 ± 2,0 °C °C | on |
| HDD/CSD | 20 °C | 20 °C, normal cotton program, 1200rpm | 30 °C, normal cotton program, 1200rpm | 20,0 ± 2,0 °C | 20,0 ± 2,0 °C | on |
| HDD/CSD | 15 °C | 20 °C, normal cotton program, 1200rpm | 30 °C, normal cotton program, 1200rpm | 15,0 ± 2,0 °C | 20,0 ± 2,0 °C | off |

| | | | | | | |
|-----|-------|---------------------------------|---------------------------------|---------------|---------------|-----|
| LDD | 30 °C | 30 °C, delicate program, 600rpm | 30 °C, delicate program, 600rpm | 20,0 ± 2,0 °C | 20,0 ± 2,0 °C | on |
| LDD | 20 °C | 20 °C, delicate program, 600rpm | 30 °C, delicate program, 600rpm | 20,0 ± 2,0 °C | 20,0 ± 2,0 °C | on |
| LDD | 15 °C | 20 °C, delicate program, 600rpm | 30 °C, delicate program, 600rpm | 15,0 ± 2,0 °C | 20,0 ± 2,0 °C | off |

* of the washing machine of the test product

3.14 Pre-treatment

- Pre-treatment of ballast load (cotton and polyester) and standard cotton fabric for HDD/CSD or LDD should be done in 3 washes at 60 °C, normal cotton programme without pre-wash.

The basic powder, optical brightener-free, of European Colour fastness Establishment (ECE) standard detergent for colour fastness (ISO 6330) of a dosage of 85g per 4,0 kg load is used (95,6 g of detergent per 4,5 kg load)

It is recommended to dry ballast load after pre-treatment.

3.15 Drying and flattening

No tumble drying for all textiles.

Stains: ironing after the wash cycle at 2 points (150 °C) without steam except for those whose colour will be affected (e.g. blood and tomato).

Standard cotton: line drying at the end of the day, no ironing.

AISE dyes: line drying at the end of the day – no ironing

4. Methods

4.1 Stain removal and basic degree of whiteness by using a spectrophotometer

4.1.1 Test procedure

The monitors used for the evaluation of the stain removal, must be chosen from the same production lot.

The appropriate amount is stored at low temperatures (according to the suppliers' recommendations) under the exclusion of light and oxygen. The material is cut into pieces of (12x12) or (5x5) cm and stored until ready for use in the dark and cold.

Two test monitors of each kind are used for every single wash and fixed on different huckaback towel carrier fabrics with the marked right side upwards.

An extra set of four carrier fabrics will be used for the next wash cycle in order to dry the first set in the meantime.

The prepared carrier fabric with the test swatches are evenly distributed in the wash load and washed in the respective programme parallel to washes at the same conditions using the reference detergent. After one wash they are removed from the machine. Afterwards the monitors are removed from the carrier and ironed (2 points, 150 °C without steam) after each wash cycle.

For stain removal, the whole procedure is repeated 6 times (for HDD/CSD and LDD washes 6 to 11).

The cotton fabrics used for the evaluation of basic degree of whiteness must be from the same production lot. The appropriate amount is stored according to the suppliers' recommendations, under exclusion of light and oxygen.

Two tests fabrics will be used for all the cycles (15 cycles).

4.1.2 Reflectance measurement

Final Y-value measurement for stain removal and basic degree of whiteness, and stain removers determination can be described as follows:

- Measuring geometry: d/8°
- D65/10° observer

- With UV-filter (420nm cut off)
- Measuring diameter: Minimum 20 mm
- Gloss: without
- Calibration: Measurements shall be carried out at the latest 8h after calibration with white tile and black trap

For each standard stain (12x12cm or 5x5cm) the mean of the 48 measurements (2 samples per soil x 4 readings x 6 wash cycles) is calculated. Standard deviation ought to be calculated from 6 washes.

For each natural stain (5 cm of diameter) the mean of the 24 measurements (2 samples per soil x 2 readings x 6 wash cycles) is calculated.

For each white cotton cloth the mean of 8 initial measurements (before first cycle) and 8 final measurements (after 15 cycles) is calculated (2 samples x 4 readings). It is necessary to bend the cotton cloth before starting with the measurements

Ganz-Griesser calculations are recommended.

4.2 Colour maintenance by using a spectrophotometer

Defined monitor set (see **Table 8**) and ballast load (see **Table 2**).

After 15 wash cycles the samples are measured using a spectrophotometer on a defined white background⁶ at four defined spots. For all products in comparison a common calibration is used. The wash temperature shall be 30°C. The measurement for the colour maintenance test will be done according to EN ISO 105-J01:2000 "*Textiles. Tests for colour fastness, general principles for measurement of surfaced colour*". The measurement conditions will be as follows:

- Measuring geometry: d/8°
- D65/10° observer
- With UV-filter (420 nm cut off)
- Measuring diameter: minimum 20 mm
- Gloss: without
- Calibration: measurements shall be carried out at the latest 8h after calibration with white tile and black trap
- Results must be reported as "grey scale" figures

The colour differences are calculated according to EN ISO 105-J03: 2009 "*Textiles. Test of colour fastness. Calculation of colour differences*". The initial state of the colour is taken as a reference for determining the colour differences, the change in colour is instrumentally assessed as described in EN ISO 105-A05:1997 "*Textiles. Test of colour fastness. Instrumental assessment of change of colour for determination of grey scale rating*". Mean and standard deviation for each dye is calculated. Mean over the complete dye set is calculated. They are based on EN 20105-A02: 1995 "*Textiles. Test of colour fastness. Grey scale for assessing change in colour*".

4.3 Dye transfer inhibition by using a spectrophotometer

Laundering device: line-test tergotometer

The laundering device is described in EN ISO 105:C06:1997 "*Textiles. Test of colour fastness. Colour fastness to domestic and commercial laundering*". A water bath containing a routable shaft which supports, radially stainless steel containers (diameter 7,5 ± 0,5 cm, height 12,0 ± 0,5 cm) with 525 ± 50 ml capacity each), the bottom of the containers is being 4.5 ± 1 cm from the centre of the shaft. The shaft/container assembly is rotated at a frequency of 40 ± 2 rpm. The temperature of the water bath is thermostatically controlled to maintain the test solution at the prescribed temperature ±2 °C.

⁶ A defined white background means the white background used by the laboratory. It should be the same for each measurement

The same liquor concentration and water hardness is used as in the washing machine. The product in test (amount for 1l) is dispersed in 1l of lukewarm water using a magnetic stirrer and then rapidly heated until the liquor reaches 40 °C.

Dye donator (0.3 g) and dye acceptor (cotton and polyamide) are placed in the container (no addition of steel balls). Both textiles are not fixed to each other. The volume to give the correct liquor: fabric ratio 100:1 is added and the containers are placed in the preheated (40 °C) machine. Temperature raises 2 °C up to 60 °C and the wash is continued for 20 min at this temperature.

Table 16. DTI wash cycle composition (detergent: CSD (powder and liquid) /LDD

| Cycle nr | 1 | 2 | 3 |
|-------------|----------------------------|---|---|
| Composition | Cotton + polyamide donator | | |

Both dye acceptors (CO and PA) are used for all 4 dye donators.

After washes the textiles are removed and rinsed twice for 1 min in running warm water and then in cold running water for 10 min (same hardness as the test). Textiles are dried hanging in the air (no direct sun)

To assess the dye transfer after one wash, colour differences between the standard cotton or polyamide piece washed without and with dye donator is determined by using a spectrophotometer.

Results must be reported as "grey scale" figures. The colour differences are calculated according to EN ISO 105-J03: 2009 "*Textiles. Test for colour fastness. Calculation of colour differences*". Measurements are taken at two defined areas of the dye acceptor using an appropriate device as described in CIE 15:2004 "colorimetry".

The instrumental assessments on colour fastness are done according to EN ISO 105-A04:1997 "*Textiles. Method for the instrumental assessment of the degree of staining of adjacent fabrics*". They are based on EN 20105-A03:1995 "*Textiles. Test for colour fastness. Grey scale for assessing staining*". The measurement for all products to be compared is performed using one common calibration under the same conditions.

- Measuring geometry: d/8°
- D65/10° observer
- With UV-filter (420nm cut off)
- Measuring diameter: minimum 20 mm
- Gloss: without
- Calibration: measurements shall be carried out at the latest 8h after calibration with white tile and black trap

4.4 Testing of stain removal, basic degree of whiteness, colour maintenance and dye transfer inhibition by using a multi-image analysis device.

A multi-image analysis device can be used to perform the above mentioned analyses. The multi-image analysis device should give similar output as a spectrophotometer.

5. Evaluation

Each product must achieve the following results

5.1 Stain removal

Each product category (HDD, CSD, LDD) follows the same procedure

All the stains must be evaluated separately (Y-final) and referred to the reference detergent and the statistical influence (σ) must be taken into account (3 failures are allowed)

$$\Delta Y = (\text{average reference} - \sigma) - (\text{average product} + \sigma)$$

$$\Delta Y \leq 10 \text{ to pass the test}$$

5.2 Basic degree of whiteness

Each product category (HDD, CSD, LDD) follows the same procedure.

$$\Delta Y = (\text{average reference} - \text{average product})$$

The product passes the test if:

- For HDD powder products: $\Delta Y < 2,0$
- For HDD liquid and CSD (powder and liquid) products: $\Delta Y < 3,0$
- For LDD products: $\Delta Y < 2,0$

5.3 Colour maintenance

Each product category (CSD and HDD/LDD) follows the same procedure.

All dyes must be evaluated separately and referred to reference detergent. The colour maintenance is measured as

$$(\Delta \text{ grey scale}) = \text{average reference} - \text{average product}$$

Each product category must achieve: $\Delta \text{ grey scale} \leq 1,0$ to pass the test (2 failures are allowed)

5.4 Dye transfer inhibition (DTI)

Each product category (CSD and HDD/LDD) follows the same procedure.

Each DTI data must be evaluated separately and compared to the reference detergent. The dye transfer inhibition is measured as

$$(\Delta \text{ grey scale}) = \text{average reference} - \text{average product}$$

Each product category must achieve: $\Delta \text{ grey scale} \leq 1,0$ to pass the test (1 failure is allowed on maximum 1 (out of 4) dye)

See Annex 1 for a complete example.

6. Results and reporting

An excel sheet template can be found on the EU Ecolabel website to report the data of the performance test of laundry detergents. The filled in template together with the requirements of the laboratory to conduct the performance test shall be provided by the applicant.

Annex 1. Example CSD liquid and template example

A template for reporting the description of the procedures and the results of the tests is available [here](http://ec.europa.eu/environment/ecolabel/documents/performance%20test%20LD.xlsx)

(<http://ec.europa.eu/environment/ecolabel/documents/performance%20test%20LD.xlsx>).

This template is not mandatory to show compliance with criterion 6 Fitness for use

Revised EU Ecolabel protocol for testing stain removers⁷

Content

- 0. Background
- 1. Test criteria
- 2. Laboratory requirements to conduct the testing.
- 3. Materials and conditions
- 4. Methods
- 5. Evaluation
- 6. Results and reporting
- Annex 1. Example

Abbreviations

| | | | |
|--------|---------------------------|------|-------------------------------|
| HDD | Heavy duty detergent | DTI | Dye transfer inhibition |
| CSD | Colour safe detergent | SBL | Soil ballast load |
| LDD | Light duty detergent | PC | Sodium percarbonate |
| SR | Stain removal | TAED | Tetra acetyl ethylene diamine |
| BDW | Basic degree of whiteness | PVP | Polyvinylpyrrolidone |
| CM | Colour maintenance | CO | Cotton |
| PA | Polyamide | PES | Polyester |
| PES/CO | Polyester/cotton | WO | Wool |
| SI | Silk | | |

0. Background

This test protocol serves as a proof to show compliance with the criterion "fitness for use" of the Commission Decision (EU) 2017/1218 of 23 June 2017 establishing EU Ecolabel criteria for Laundry detergents. The product shall be fit for use, meeting the needs of consumers.

The test is for products that fall under the scope of the product group "Laundry detergents" as "pre-treatment stain removers" which means stain removers used for direct spot treatment of textiles before washing in the washing machine but do not include stain removers dosed in the washing machine and stain removers dedicated to other uses besides pre-treatment. This means, this protocol focuses on stain removers as specified in the section 3.1 "Range of application".

1. Test criteria

The intention is that the test should show that stain removers make a positive contribution to the washing result. This is achieved by performing a wash test for the standard reference and comparing this result with the result of an equivalent wash test for the standard reference with a stain remover added. The wash test shall be passed for all soil types that the product is claimed to have an effect on. If no specific types of soils are specified on the product at least five different soils must be tested and the reasons for the choice of these soils must be stated.

2. Laboratory requirements to conduct the testing.

The manufacturer's test laboratory or/and an external test laboratory can be approved to conduct testing to document effectiveness of hard surface cleaners if the following requirements are met:

⁷ Not for industrial and institutional products

- it must be possible for EU Ecolabel competent bodies to monitor the performance of testing (e.g. on-site visits to the laboratory),
- the EU Ecolabel Competent Body must have access to all data on the product (e.g. technical data sheets),
- whenever possible, the samples must be made anonymous for the test laboratory (e.g. product A and product B).
- the test laboratories must be equipped with the devices described in the test method,
- performance of the effectiveness test as well as the test method must be described in the quality control system.

Competent bodies shall preferentially recognise attestations which are issued by bodies accredited in accordance with the relevant harmonised standard for testing and calibration laboratories and verifications by bodies that are accredited in accordance with the relevant harmonised standard for bodies certifying products, processes and services. Accreditation shall be carried out in accordance with Regulation (EC) No 765/2008 of the European Parliament and of the Council

3. Materials and conditions

The test institute must be able to prove the compliance with all test conditions laid down in the following paragraphs. The documentation of the compliance with all test conditions shall be part of the test report (section 6 Results and reporting).

3.1 Range of application:

In the context of the EU Ecolabel, this performance test can be applied to stain removers for clothing, for soaking as a wash enhancer or for pre-washes or other equivalent functions. Pre-treatment stain removers include stain removers used for direct spot treatment of textiles (before washing in the machine) but don't include stain removers dosed in the washing machine and stain remover dedicated to other uses besides pre-treatment.

3.2 Washing machine types:

Programmable electronic Miele⁸ household washing machines which fulfil the following requirements

Table 17. Washing machine and wash programmes specifications

| | Cotton wash program (at 30 °C, 20 °C ^a , 15 °C ^b) | Delicate program ^c (at 30 °C, 20 °C ^a , 15 °C ^b) |
|--------------------------|---|---|
| Duration main wash | 50-70 min | 30-40 min |
| Total program duration | 100-120 min | 55-65 min |
| Water quantity main wash | 15±2 l | 20±2 l |
| Total water quantity | 55±5 l | 64±5 l |
| Number of rinse cycles | 3 | 3 |
| Final spin speed | 1200rpm ⁹ | 600rpm |

^a for cold water products

⁸ Miele machine was proposed as a reference machine due to its stable performance and regular quality of the outcomes. Another machine could be used as reference machine if it provides similar performance for a comparable programme.

For use in laboratories Miele launched a special line of machines where the fuzzy logic is already disabled (e.g. Miele 1935 WPS WTL).

⁹ See footnote 2

^b most of the older machines do not offer cold water programs. Those machines which offer cold water programmes normally heat up the entering water to 21 °C, which can be used for products that claim to be effective at 20 °C. For test runs at 15 °C the heating elements of the washing machine have to be disconnected to prevent the heat up

^c some newer washing machines offer an equivalent synthetic program

3.3 Water conditions:

Water hardness: $2,5 \pm 0,2 \text{ mmol CaCO}_3/\text{l}$. The Ca/Mg ration will be $3 \pm 0,5$

Water inlet temperature: $20,0 \pm 4,0$ °C, but not for those product that claim to be effective at lower temperature. The water inlet temperature for products which are effective at lower temperature shall be $15,0 \pm 4$ °C

The amount of water shall be controlled along the washing process, if possible.

The water hardness and the water inlet temperature shall be reported for the test product and reference detergent or stain removal.

3.4 Ballast load:

Cotton ballast load: the base load of cotton shall consist of cotton pillowcases and cotton huckaback hand-towels conforming standard IEC 60456³.

3.5 Stains sets

For non-specific products, the product must be tested on a minimum of five different stains. If the product claims a specific effect, the product must be tested on a minimum of five stains of the product claim¹⁰. In any case, the reason for the choice of the stains must be given to the competent body (Section 6 Results and reporting).

Two sets of stains per wash cycle (in the same batch) should be used. Mark with a water resistant pen each stain as the Figure 1. Fix the stains on the loads with a plastic staple with a gun on the load, as the example in Figure 2. Alternatively, the stains can be stitched together beforehand to make a full test strip or use a multiswatch monitor⁵. Then, this strip must be fixed on a hand towel before washing.




Figure 1-3. Marking of the stain sets

Table 18. Information on the different stains and suppliers

| Stains | Fabric | Standard stains | | | Hand made | Type |
|----------------------------|------------|-----------------|---------|-----------|-----------|--------|
| Carbon black/ olive oil | CO | EMPA 101 | WFK 10B | CFT C-02 | 125KC | Greasy |
| | PES/ CO | EMPA 104 | WFK 20B | CFT PC-02 | 125PC | |
| | WO | EMPA 107 | WFK 30B | CFT P-02 | 125PE | |

¹⁰ For example, if the stain remover claims to be effective in removing greasy stains, stains must be chosen from the following list: carbon black/olive oil, carbon black/mineral oil, sebum/pigment, lipstick, make-up, pigment/lanolin, pigment/olive oil

| | | | | | | |
|------------------------------|------------|--|------------------------|----------------------------|-------|-----------------------|
| Carbon black/ mineral oil | CO | EMPA 106 | WFK 10M | CFT C-01 | | Greasy |
| | PES/ CO | | WFK 20M | CFT PC-02 | | |
| | PES | | WFK 30M | CFT P-02 | | |
| Blood | CO | EMPA 111 | WFK 10PBU WFK 90PBU | | 109KC | Enzymatic |
| | PES/ CO | | WFK 20PBU | | 109PC | |
| | PES | | WFK 30PBU | | 109PE | |
| Aged blood | CO | | WFK 10PB | CFT C-S-01 | | Enzymatic |
| | PES/ CO | | WFK 20PB | CFT PC-S-01 | | |
| | PES | | WFK 30PB | CFT P-S-01 | | |
| Cocoa | CO | | WFK 10MF WFK 90MF | CFT CS-02 | | Enzymatic |
| | PES/ CO | | WFK 20MF | CFT PC-S-02 | | |
| | PES | | WFK 30MF | CFT P-S-02 | | |
| Red wine | CO | EMPA 114 | WFK 10LIU WFK 90LIU | CFT C-S-103 | 126KC | Bleachable |
| | PES/ CO | | WFK 20LIU | CFT PC-S-103 | 126PC | |
| | PES | | WFK 30LIU | CFT P-S-103 | 126PE | |
| | WO | | WFK 60LIU | CFT W-S-103 | | |
| | SI | | WFK 70LIU | CFT S-S-103 | | |
| Aged red wine | CO | EMPA 122 | WFK 10LI WFK 90LI | CFT CS-03 | | Bleachable |
| | PES/CO | | WFK 20LI | CFT PC-S-03 | | |
| | PES | | WFK 30LI | CFT P-S-03 | | |
| | WO | | WFK 60LI | CFT W-S-03 | | |
| | SI | | WFK 70LIU | CFT S-S-03 | | |
| Blood/milk/ink | CO | EMPA 116 | | CFT C-05 | | Enzymatic |
| | PES/ CO | EMPA 117 | | CFT PC-05 | | |
| | PES | | | CFT P-05 | | |
| Sebum/pigment | CO | EMPA 118 | WFK 10D WFK 90D | CFT C-S-132 | | Greasy |
| | PES/CO | EMPA 119 | WFK 20D | CFT PC-S-132 | | |
| | PES | | WFK 30D | CFT P-S-132 | | |
| | WO | | WFK 60D | CFT W-S-132 | | |
| | SI | | WFK 70D | CFT S-S-132 | | |
| Lipstick | CO | EMPA 141/1 EMPA 141/2 EMPA 141/3 | WFK 10LS | CFT C-S-216 | 073KC | Greasy Particulate |
| | PES/ CO | EMPA 142/1 EMPA 142/2 EMPA 142/3 | WFK 20LS | CFT PC-S-216 | 073PC | |
| | PES | | WFK 30LS | CFT P-S-216 CFT P-S-116 | 073PE | |
| | WO | | WFK 60LS | CFT W-S-216 CFT W-S-116 | | |
| | SI | | WFK 70LS | CFT S-S-216 CFT S-S-116 | | |
| Make up | CO | EMPA 143/1 EMPA 143/2 EMPA 143/3 | WFK 10MU | CFT C-S-17 | 075KC | Greasy Particulate |

| | | | | | | |
|---|------------|--|------------------------|--------------|-------------|-------------------------|
| | PES/ CO | EMPA 144/1 EMPA 144/2 EMPA 144/3 | WFK 20MU | CFT PC-S-17 | 075PC | |
| | PES | | WFK 30MU | CFT P-S-17 | 075PE | |
| | WO | | WFK 60MU | CFT W-S-17 | | |
| | SI | | WFK 70MU | CFT S-S-17 | | |
| Chocolate cream | CO | EMPA 160 | | CFT C-S-68 | CFT KC-H009 | Enzymatic |
| Chocolate | CO | | WFK 10Z | CFT C-S-44 | 033KC | Enzymatic |
| | PES/CO | | WFK 20Z | CFT PC-S-44 | 033PC | |
| | PES | | WFK 30Z | CFT P-S-44 | 033PE | |
| | WO | | WFK 60Z | CFT W-S-44 | | |
| | SI | | WFK 70Z | CFT S-S-44 | | |
| Cocoa, not temperature treated | CO | EMPA 112 | WFK 10MFU WFK 90MFU | | 038KC | Enzymatic |
| | PES/CO | | WFK 20MFU | | 038PC | |
| | PES | | WFK 30MFU | | 038PE | |
| Corn starch | CO | EMPA 161 | WFK 10R | CFT C-S-26 | | Enzymatic |
| | PES/CO | EMPA 162 | WFK 20R | CFT PC-S-26 | | |
| | PES | | WFK 30R | CFT P-S-26 | | |
| Potato starch | CO | | | CFT C-S-27 | | Enzymatic |
| | PES/CO | | | CFT PC-S-27 | | |
| | PES | | | CFT P-S-27 | | |
| Rice starch | CO | | | CFT C-S-28 | CFT KC-H161 | Enzymatic |
| | PES/ CO | | | CFT PC-S-28 | CFT PC-H161 | |
| | PES | | | CFT P-S-28 | CFT P-H161 | |
| Porridge | CO | EMPA 163 | | | 097KC | Enzymatic |
| Grass | CO | EMPA 164 | | CFT C-S-08 | 062KC | Bleachable Enzymatic |
| | PES/ CO | | | CFT PC-S-08 | 062PC | |
| | PES | | | CFT P-S-08 | 062PE | |
| Pudding (mananase sensitive) | CO | EMPA 165 | | CFT C-S-69 | CFT C-H118 | Enzymatic |
| Tea (responsive to bleach only due to special treatment) | CO | | | CFT C*BC-03 | 117KC | Bleachable |
| | PES/CO | | | CFT PC-BC-03 | 117PC | |
| | PES | | | CFT P-BC-03 | 117PE | |
| | SI | | | | | |
| Tea | CO | EMPA 167 | WFK 10J | CFT C-S-97 | | Bleachable |
| | PES/ CO | EMPA 168 | WFK 20J | CFT PC-S-97 | | |
| | PES | | WFK 30J | CFT P-S-97 | | |
| Pigment/ lanolin | CO | | WFK 10C | | | Greasy |
| | PES/ CO | | WFK 20C | | | |
| | PES | | WFK 30C | | | |
| | WO | | WFK 60C | | | |
| | SI | | WFK 70C | | | |

3.6 Stains set size

(12x12) cm², (5x5) cm² standard stains and colour maintenance and 5 cm diameter (hand-made).

3.7 Soil

Introduce 4 sheets of SBL 2004 per wash. The supplier of SBL 2004 is WFK (<http://www.testgewebe.de>). Fix the SBL sheets on the loads as the stains.

3.8 Wash loads

Each test series has to be started with a new wash load. This load consists of:

1. A new all cotton ballast load for the normal cotton wash program to reach a total weight of 4,5 kg.

Table 19. Total cotton loads (kg)

| Total load (kg) | Pillowcases | Hand-towel |
|-----------------|-------------|--------------|
| 4,5 kg ±0,1kg | 12 units | Until weight |

2. 5 stain removal monitors x 2 replicates

3. 4 pieces of soil ballast

The total load per wash including ballast load, SBL, cotton cloth and monitors will be 4,5 ±0,1 kg.

3.9 Pre-treatment of cotton hand towels and ballast load

3 washes at 60 °C, normal cotton program without pre-wash. The basic powder, optical brightener-free, of ECE-2 standard detergent for colour fastness (ISO 6330) of a dosage of 85g per 4,0 kg load is used (95,6 g of detergent per 4,5 kg load)

It is recommended to dry ballast load after pre-treatment. A standard dryer can be used.

3.10 Reference detergent

Table 20. Reference detergent

Regular standard powder detergent IEC P (that can serve as reference for a detergent to wash white fabrics). This standard detergent is distributed as three separate components (because of stability of storage) with the following composition:

- 82% IEC P BASE powder with enzyme and foam inhibitor (= IEC A* BASE, see table below)
- 15% sodium percarbonate
- 3% bleach activator tetra-acetythylenediamine (TAED)

| Ingredient | % content | Tolerance (+/-) | CAS n. |
|---|-----------|-----------------|-------------|
| linear sodium alkyl benzene sulfonate | 11,4 | 0,5 | 25155-30-0 |
| ethoxylated fatty alcohol C _{12/14} (7EO) | 6,1 | 0,3 | 68439-50-9 |
| sodium soap (tallow soap) | 4,2 | 0,2 | 308075-99-2 |
| foam inhibitor concentrate, 12% silicon on inorganic carrier) | 5,1 | 0,3 | 68989-22-0 |
| sodium aluminium silicate zeolite 4A (80% active substance) | 36,7 | 1 | 70955-01-0 |
| sodium carbonate | 15,1 | 1 | 497-19-8 |
| sodium salt of a copolymer from acrylic and maleic acid (sokalan CP5) | 3,1 | 0,2 | 60472-42-6 |
| sodium silicate (SiO ₂ :Na ₂ O = 3.3:1) | 3,9 | 0,2 | 1344-09-8 |
| carboxymethylcellulose | 1,6 | 0,1 | 9004-32-4 |
| phosphonate (25% active acid) | 3,6 | 0,2 | 22042-96-2 |
| protease | 0,5 | 0,5 | 9014-01-1 |
| sodium sulfate | rest | rest | 7757-82-6 |

The ingredients shall be mixed prior to use. The maximum storage time after mixing is 7 days.

Dosage HDD: 70 g of powder base

Put detergent in dispenser machine device.

3.11 Test product for stain removers

The test product consists of a reference detergent with a stain remover added. The reference detergent is dosed as in 3.10. The stain remover is dosed according to the instructions provided on the product and taking into account consumer habits.

3.12 Wash programme

30 °C, cotton normal program and final spin 1200rpm.

3.13 Procedures

- Pre-treatment of cotton and hand-towels and ballast load according to section 3.9.
- Washing: The following wash cycles are run, at least, 6 times with each product, using a new set of stains each time. For all the different products in

Table 21, 5x2 different stains (according to 2.5) must be tested and 2 standard cotton cloths in the same wash (according to 2.8)

Table 21. Washing conditions

| Product | Conditions |
|---|--|
| Stain remover + reference detergent (IEC P BASE according to 60456) | In this case the stain remover following the recommendations from the producer and wash adding 70g of reference detergent (Table 20) |
| Reference detergent (IEC P BASE according to 60456) | In this case wash adding only 70g of reference detergent (Table 20) |
| Water | Wash without chemical products (detergents and additives) |

- Drying (no tumble drying) and flattening: 2 points (150 °C) without steam after each wash cycle just the stains

4. Methods

4.1 Test procedure

The stain sets monitors used for the evaluation must be from the same production lot. The appropriate amount is stored at low temperatures (according to the recommendations of the suppliers) under exclusion of light and oxygen. The material is cut into pieces of 12x12cm and stored until ready to use in the dark and cold.

Two test monitors of each kind are used for every single wash and fixed on different huckaback towel carrier fabrics with the marked right side upwards.

An extra set of four carrier fabrics will be used for the next wash cycle in order to dry the first set in the meantime.

The prepared carrier fabric with the test swatches are evenly distributed in the wash load and washed in the run programme while to washes at the same conditions using the reference detergent. After one wash they are removed from the machine. Afterwards the monitors are removed from the carrier and dried in the dark at ambient conditions lying flat on a sieve.

For the test, the whole procedure is repeated 6 times.

4.2 Reflectance measurement

Final Y-value measurement for stain removal determination can be described as follows:

- Measuring geometry: d/8°
- D65/10° observer
- With UV-filter (420 nm cut off)
- Measuring diameter: minimum 20 mm
- Gloss: without
- Calibration: measurements shall be carried out at the latest 8h after calibration with white tile and black trap

For each soil monitor the mean of the 48 measurements (2 samples per soil x 4 readings x 6 wash cycles) are calculated. Standard deviation ought to be calculated from 6 washes.

The mean value (Y) for the above measurements is taken for each stain test. The normalized wash result is achieved by subtracting the result for water from both the reference detergent and the test product.

5. Evaluation

The product will be considered to have a satisfactory performance, at temperature tested, if it achieves the following results:

The general normalized cleaning effect must be greater than 110% compared to the reference detergent and the result for all soil types must be better than for water.

6. Results and reporting

An excelsheet template can be found on the EU Ecolabel website to report the data of the performance test of laundry detergents. The filled in template together with the requirements of the laboratory to conduct the performance test shall be provided by the applicant.

Annex 1: Examples for reporting

A template for reporting the description of the procedures and the results of the tests is available [here](http://ec.europa.eu/environment/ecolabel/documents/performance%20test%20LD.xlsx)

(<http://ec.europa.eu/environment/ecolabel/documents/performance%20test%20LD.xlsx>).

This template is not mandatory to show compliance with criterion 6 Fitness for use